

**Trade name:** 75000-00104, ink, green

**Product no.:** 75000-00104

**Current version :** 1.0.0, issued: 22.07.2021

**Replaced version:** -, issued: -

**Region:** IE

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**75000-00104, ink, green**

**UFI:**

**NHP5-X0SP-K00J-255M**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

printer's ink

Ink

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

Paul Leibinger GmbH & Co. KG

Daimlerstrasse 14

78532 Tuttlingen

Telephone no. +49 (0)7461 9286 0

Fax no. +49 (0)7461 9286 119

e-mail info@leibinger-group.com

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

+353 1 809 2166 (National Poisons Information Centre)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Eye Irrit. 2; H319

Flam. Liq. 2; H225

STOT SE 3; H336

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**



GHS02



GHS07

**Signal word**

Danger

**Hazardous component(s) to be indicated on label:**

acetone

Trade name: 75000-00104, ink, green

Product no.: 75000-00104

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

**Hazard statement(s)**

H225 Highly flammable liquid and vapour.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.

**Hazard statements (EU)**

EUH066 Repeated exposure may cause skin dryness or cracking.  
 EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Precautionary statement(s)**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P240 Ground and bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ventilating/lighting/ equipment.  
 P242 Use non-sparking tools.  
 P243 Take action to prevent static discharges.  
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.

**UFI:**

NHP5-X0SP-K00J-255M

**2.3 Other hazards**

PBT assessment  
 No data available.

vPvB assessment  
 No data available.

**SECTION 3: Composition/information on ingredients****3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures****Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	<b>acetone</b>		
	67-64-1 200-662-2 606-001-00-8 -	EUH066 Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	>= 25,00 - < 50,00 wt%
2	<b>ethanol</b>		
	64-17-5 200-578-6 603-002-00-5 -	Flam. Liq. 2; H225	>= 10,00 - < 25,00 wt%
3	<b>ethyl-acetate</b>		
	141-78-6 205-500-4 607-022-00-5 -	EUH066 Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	>= 5,00 - < 25,00 wt%
4	<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]</b>		
	13463-67-7 236-675-5	Carc. 2; H351i	>= 5,00 - < 10,00 wt%

Trade name: 75000-00104, ink, green

Product no.: 75000-00104

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

	022-006-00-2 -			
5	<b>1-methoxy-2-propanol</b>			
	107-98-2 203-539-1 603-064-00-3 -	Flam. Liq. 3; H226 STOT SE 3; H336	< 5,00	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
4	V, W, 10	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
4	H351i inhalational; -, -

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. In case of persisting adverse effects, consult a physician.

#### After inhalation

Remove affected persons from dangerous area by observing suitable respiratory protection measures. Ensure supply of fresh air.

#### After skin contact

In case of contact with skin wash off with water.

#### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Get medical attention if pain still persists.

#### After ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray

#### Unsuitable extinguishing media

High power water jet

### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO)

### 5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Containers close to fire should be transferred to a safe place. Cool closed containers exposed to fire with water.

## SECTION 6: Accidental release measures

Trade name: 75000-00104, ink, green

Product no.: 75000-00104

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Keep away from ignition sources.

**For emergency responders**

Personal protective equipment (PPE) - see section 8.

**6.2 Environmental precautions**

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

**6.3 Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

**6.4 Reference to other sections**

Information regarding safe handling, see section 7. Information regarding personal protective measures, see section 8. Information regarding waste disposal, see section 13.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling****Advice on safe handling**

Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

**General protective and hygiene measures**

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Do not inhale vapours. Avoid contact with eyes and skin. Wash hands before breaks and after work. Remove contaminated clothing and shoes and launder thoroughly before reusing.

**Advice on protection against fire and explosion**

Keep away from ignition sources and provide for good ventilation. Vapours can form an explosive mixture with air. Isolate from sources of heat, sparks and open flame. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Use explosion-proof equipment/fittings and non-sparking tools.

**7.2 Conditions for safe storage, including any incompatibilities****Technical measures and storage conditions**

Keep container tightly closed and dry in a cool, well-ventilated place.

**Recommended storage temperature**

Value 10 - 25 °C

**Requirements for storage rooms and vessels**

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

**Incompatible products**

Substances to be avoided, see section 10.

**7.3 Specific end use(s)****Recommendations**

Ink for industrial CIJ printers

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	acetone	67-64-1	200-662-2
	2000/39/EC		
	Acetone		

Trade name: 75000-00104, ink, green

Product no.: 75000-00104

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

	WEL long-term (8-hr TWA reference period)	1210	mg/m <sup>3</sup>	500	ppm
<b>List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)</b>					
Acetone					
	WEL long-term (8-hr TWA reference period)	1210	mg/m <sup>3</sup>	500	ppm
	Comments	IOELV			
<b>2</b>	<b>ethanol</b>	<b>64-17-5</b>		<b>200-578-6</b>	
<b>List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)</b>					
Ethanol					
	WEL short-term (15 min reference period)			1000	ppm
<b>3</b>	<b>ethyl-acetate</b>	<b>141-78-6</b>		<b>205-500-4</b>	
<b>2017/164/EU</b>					
Ethyl acetate					
	WEL short-term (15 min reference period)	1468	mg/m <sup>3</sup>	400	ppm
	WEL long-term (8-hr TWA reference period)	734	mg/m <sup>3</sup>	200	ppm
<b>List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)</b>					
Ethyl acetate					
	WEL short-term (15 min reference period)	1468	mg/m <sup>3</sup>	400	ppm
	WEL long-term (8-hr TWA reference period)	734	mg/m <sup>3</sup>	200	ppm
	Comments	IOELV			
<b>4</b>	<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]</b>	<b>13463-67-7</b>		<b>236-675-5</b>	
<b>List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)</b>					
Titanium dioxide					
total inhalable dust					
	WEL long-term (8-hr TWA reference period)	10	mg/m <sup>3</sup>		
<b>List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)</b>					
Titanium dioxide					
respirable dust					
	WEL long-term (8-hr TWA reference period)	4	mg/m <sup>3</sup>		
<b>5</b>	<b>1-methoxy-2-propanol</b>	<b>107-98-2</b>		<b>203-539-1</b>	
<b>2000/39/EC</b>					
1-Methoxypropanol-2					
	WEL short-term (15 min reference period)	568	mg/m <sup>3</sup>	150	ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup>	100	ppm
	Skin resorption / sensibilisation	Skin			
<b>List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)</b>					
Propylene glycol monomethyl ether					
	WEL short-term (15 min reference period)	568	mg/m <sup>3</sup>	150	ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup>	100	ppm
	Comments	IOELV			

**8.2 Exposure controls**

**Appropriate engineering controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

**Personal protective equipment**

**Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

**Eye / face protection**

Safety glasses with side protection shield (EN 166)

**Hand protection**

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-

**Trade name:** 75000-00104, ink, green

**Product no.:** 75000-00104

**Current version :** 1.0.0, issued: 22.07.2021

**Replaced version:** -, issued: -

**Region:** IE

station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

**Other**

Normal chemical work clothing.

**Environmental exposure controls**

No data available.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

<b>State of aggregation</b>	
liquid	
<b>Form/Colour</b>	
green	
<b>Odour</b>	
acetone-like	
<b>pH value</b>	
No data available	
<b>Boiling point / boiling range</b>	
Value	> 56 °C
Source	supplier
<b>Melting point/freezing point</b>	
No data available	
<b>Decomposition temperature</b>	
No data available	
<b>Flash point</b>	
Value	-12 °C
Source	supplier
<b>Ignition temperature</b>	
Value	> 300 °C
Source	supplier
<b>Explosive properties</b>	
This product is not explosive. In and after use danger of production of inflammable compounds.	
<b>Flammability</b>	
No data available	
<b>Lower explosion limit</b>	
Value	1 % vol
Source	supplier
<b>Upper explosion limit</b>	
Value	15 % vol
Source	supplier
<b>Vapour pressure</b>	
Value	<= 240 hPa
Source	supplier
<b>Relative vapour density</b>	
No data available	
<b>Relative density</b>	

Trade name: 75000-00104, ink, green

Product no.: 75000-00104

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

No data available

Density			
Value	0,92	-	0,97 g/cm <sup>3</sup>
Reference temperature			20 °C
Source	supplier		

**Solubility**  
No data available

**Partition coefficient n-octanol/water (log value)**  
No data available

Viscosity			
Value	4	-	8 mPa*s
Source	supplier		

Solvent content			
Value	63	-	76 %

**Particle characteristics**  
No data available

## 9.2 Other information

Other information
VOC: 63 - 76 % (579,6 - 737,2 g/l)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Dangerous reactions are not expected if the product is handled according to its intended use.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

Dangerous reactions are not to be expected when handling product according to its intended use.

### 10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

### 10.5 Incompatible materials

Oxidizing agents

### 10.6 Hazardous decomposition products

None, if handled according to intended use.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute oral toxicity**  
No data available

**Acute dermal toxicity**  
No data available

**Acute inhalational toxicity**  
No data available

**Skin corrosion/irritation**  
No data available

**Serious eye damage/irritation**  
No data available

Trade name: 75000-00104, ink, green

Product no.: 75000-00104

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

<b>Respiratory or skin sensitisation</b>
No data available
<b>Germ cell mutagenicity</b>
No data available
<b>Reproduction toxicity</b>
No data available
<b>Carcinogenicity</b>
No data available
<b>STOT - single exposure</b>
No data available
<b>STOT - repeated exposure</b>
No data available
<b>Aspiration hazard</b>
No data available

**11.2 Information on other hazards**

**Endocrine disrupting properties**

No data available.

**Other information**

No data available.

**SECTION 12: Ecological information**

**12.1 Toxicity**

<b>Toxicity to fish (acute)</b>
No data available
<b>Toxicity to fish (chronic)</b>
No data available
<b>Toxicity to Daphnia (acute)</b>
No data available
<b>Toxicity to Daphnia (chronic)</b>
No data available
<b>Toxicity to algae (acute)</b>
No data available
<b>Toxicity to algae (chronic)</b>
No data available
<b>Bacteria toxicity</b>
No data available

**12.2 Persistence and degradability**

No data available.

**12.3 Bioaccumulative potential**

No data available.

**12.4 Mobility in soil**

No data available.

**12.5 Results of PBT and vPvB assessment**

<b>Results of PBT and vPvB assessment</b>	
PBT assessment	No data available.
vPvB assessment	No data available.

**Trade name:** 75000-00104, ink, green

**Product no.:** 75000-00104

**Current version :** 1.0.0, issued: 22.07.2021

**Replaced version:** -, issued: -

**Region:** IE

## 12.6 Endocrine disrupting properties

No data available.

## 12.7 Other adverse effects

No data available.

## 12.8 Other information

### Other information

Do not discharge product unmonitored into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

#### Packaging

Used, completely emptied, packaging may be disposed of or passed to recovery systems in compliance with national and local provisions related to waste legislation. Like the unused product, the packaging that has not been emptied, may be disposed of or passed to recovery systems in compliance with national and local provisions related to waste legislation.

## SECTION 14: Transport information

### 14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1210
Proper shipping name	PRINTING INK
Special Provision 640	640C
Tunnel restriction code	D/E
Label	3

### 14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1210
Proper shipping name	PRINTING INK
EmS	F-E, S-D
Label	3

### 14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1210
Proper shipping name	Printing ink
Label	3

### 14.4 Other information

No data available.

### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

### 14.6 Special precautions for user

No data available.

### 14.7 Maritime transport in bulk according to IMO instruments

Trade name: 75000-00104, ink, green

Product no.: 75000-00104

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

Not relevant

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

##### Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

##### REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

##### Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
----------------------------------------------------------------------------------------	----------

##### Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P5b
--------------------------------------------------------------	-----

##### Other regulations

Adhere to the national sanitary and occupational safety regulations when using this product.

### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

## SECTION 16: Other information

#### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

#### Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226 Flammable liquid and vapour.

H351i Suspected of causing cancer by inhalation.

#### Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

V If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

W It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.  
This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

1 The concentration stated or, in the absence of such concentrations, the generic concentrations of this Regulation (Table 3.1) or the generic concentrations of Directive 1999/45/EC (Table 3.2), are the percentages by weight of the metallic element calculated

---

**Trade name:** 75000-00104, ink, green

**Product no.:** 75000-00104

**Current version :** 1.0.0, issued: 22.07.2021

**Replaced version:** -, issued: -

**Region:** IE

---

with reference to the total weight of the mixture.

**Creation of the safety data sheet**

UMCO GmbH - D-21107 Hamburg, Georg-Wilhelm-Strasse 187, Tel.: +49(40)555 546 300, Fax: +49(40)555 546 357, e-mail: [umco@umco.de](mailto:umco@umco.de)

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 776827