

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

77001-00117, solvent

UFI:

GVA5-606F-M005-2KRC

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

printer's ink

Thinner

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

Paul Leibinger GmbH & Co. KG

Daimlerstrasse 14

78532 Tuttingen

Telephone no. +49 (0)7461 9286 0

Fax no. +49 (0)7461 9286 119

e-mail info@leibinger-group.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

+353 1 809 2166 (National Poisons Information Centre)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Irrit. 2; H319

Flam. Liq. 2; H225

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07

Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/ equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/protective clothing/eye protection.

P370+P378 In case of fire: Use sand, fire powder, carbon dioxide or foam to extinguish.

UFI:

GVA5-606F-M005-2KRC

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	ethanol			
	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	< 100,00	wt%
2	butanone			
	78-93-3 201-159-0 606-002-00-3 01-2119457290-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	< 2,50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Eye Irrit. 2; H319: C >= 50%	-	-

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. In case of persisting adverse effects, consult a physician.

After inhalation

Remove affected persons from dangerous area by observing suitable respiratory protection measures. Ensure supply of fresh air.

After skin contact

In case of contact with skin wash off with water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Get medical attention if pain still persists.

Trade name: 77001-00117, solvent**Product no.:** 77001-00117**Current version :** 1.0.0, issued: 22.07.2021**Replaced version:** -, issued: -**Region:** IE**After ingestion**

Rinse the mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Containers close to fire should be transferred to a safe place. Cool closed containers exposed to fire with water.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Keep away from ignition sources.

For emergency responders

Personal protective equipment (PPE) - see section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

Information regarding safe handling, see section 7. Information regarding personal protective measures, see section 8. Information regarding waste disposal, see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Do not inhale vapours. Avoid contact with eyes and skin. Wash hands before breaks and after work. Remove contaminated clothing and shoes and launder thoroughly before reusing.

Advice on protection against fire and explosion

Keep away from ignition sources and provide for good ventilation. Vapours can form an explosive mixture with air. Isolate from sources of heat, sparks and open flame. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Use explosion-proof equipment/fittings and non-sparking tools.

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place.

Recommended storage temperature

Value 15 - 25 °C

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Substances to be avoided, see section 10.

7.3 Specific end use(s)

Recommendations

Solvent for industrial CIJ printers

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)			
Ethanol			
	WEL short-term (15 min reference period)		1000 ppm
2	butanone	78-93-3	201-159-0
2000/39/EC			
Butanone			
	WEL short-term (15 min reference period)	900 mg/m ³	300 ppm
	WEL long-term (8-hr TWA reference period)	600 mg/m ³	200 ppm
List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)			
Methyl ethyl ketone			
	WEL short-term (15 min reference period)	900 mg/m ³	300 ppm
	WEL long-term (8-hr TWA reference period)	600 mg/m ³	200 ppm
	Comments	Sk, IOELV	

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	ethanol	64-17-5 200-578-6		
	dermal	Long term (chronic)	systemic	343 mg/kg/day
	inhalative	Long term (chronic)	systemic	950 mg/m ³
2	butanone	78-93-3 201-159-0		
	dermal	Long term (chronic)	systemic	1161 mg/kg/day
	inhalative	Long term (chronic)	systemic	600,00 mg/m ³

DNEL value (consumer)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	ethanol	64-17-5 200-578-6		
	oral	Long term (chronic)	systemic	87 mg/kg/day
	dermal	Long term (chronic)	systemic	206 mg/kg/day

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

	inhalative	Long term (chronic)	systemic	114	mg/m ³
2	butanone			78-93-3 201-159-0	
	oral	Long term (chronic)	systemic	31	mg/kg/day
	dermal	Long term (chronic)	systemic	412	mg/kg/day
	inhalative	Long term (chronic)	systemic	106	mg/m ³

PNEC values

No	Substance name	ecological compartment		Type	CAS / EC no	Value
1	ethanol				64-17-5 200-578-6	
	water	fresh water			0,96	mg/L
	water	Aqua intermittent			2,75	mg/L
	water	marine water			0,79	mg/L
	water	fresh water sediment			3,6	mg/kg dry weight
	water	marine water sediment			2,9	mg/L
	soil	-			0,63	mg/kg dry weight
	sewage treatment plant	-			580	mg/L
	secondary poisoning	-			0,38	mg/kg food
2	butanone				78-93-3 201-159-0	
	water	fresh water			55,8	mg/L
	water	marine water			55,8	mg/L
	water	Aqua intermittent			55,8	mg/L
	water	fresh water sediment			284,74	mg/kg
	with reference to: dry weight					
	water	marine water sediment			284,7	mg/kg
	with reference to: dry weight					
	soil	-			22,5	mg/kg
	with reference to: dry weight					
	sewage treatment plant	-			709	mg/L
	secondary poisoning	-			1000	mg/kg
	with reference to: food					

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Respirator A2

Eye / face protection

Tightly fitting safety glasses (EN 166).

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material butyl rubber

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

Material thickness	>	0,5	mm
Breakthrough time	>=	60	min

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form/Colour	
colourless, clear	
Odour	
alcohol-like	
pH value	
No data available	
Boiling point / boiling range	
No data available	
Melting point/freezing point	
No data available	
Decomposition temperature	
No data available	
Flash point	
Value	supplier 12 °C
Source	supplier
Ignition temperature	
Value	supplier 425 °C
Source	supplier
Flammability	
No data available	
Lower explosion limit	
Value	supplier 3,5 % vol
Source	supplier
Upper explosion limit	
Value	supplier 15 % vol
Source	supplier
Vapour pressure	
No data available	
Relative vapour density	
No data available	
Relative density	
No data available	
Density	
Value	supplier 0,8 g/cm ³
Source	supplier
Solubility in water	
Source	supplier

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

Comments	miscible
----------	----------

Solubility
No data available

Partition coefficient n-octanol/water (log value)
--

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
log Pow		-0,35	
Reference temperature		24	°C
with reference to			
Method		pH 7,4	
Source		OECD 107	
		ECHA	
2	butanone	78-93-3	201-159-0
log Pow		0,3	
Reference temperature		40	°C
Method		OECD 117	
Source		ECHA	

Viscosity			
Value	~	1	mPa*s
Type	dynamic		
Source	supplier		

Solvent content		
Value	100	%

Particle characteristics
No data available

9.2 Other information

Other information
VOC: 100 %

SECTION 10: Stability and reactivity

10.1 Reactivity

Dangerous reactions are not expected if the product is handled according to its intended use.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Dangerous reactions are not to be expected when handling product according to its intended use.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

strong oxidizing agents

10.6 Hazardous decomposition products

None, if handled according to intended use.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LD50		10470	mg/kg bodyweight
Species	rat		

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

with reference to Method Source Evaluation/classification	95% ethanol in water OECD 401 ECHA Based on available data, the classification criteria are not met.
2 butanone	78-93-3 201-159-0
LD50	2054 mg/kg bodyweight
Species	rat
Method	OECD 423
Source	ECHA / Read across

Acute dermal toxicity	
No data available	

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		124,7	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2 butanone	78-93-3	201-159-0	
Duration of exposure		4	h
Species	rabbit		
Method	OECD 404		
Source	ECHA / Read across		
Evaluation	non-irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		
2 butanone	78-93-3	201-159-0	
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Route of exposure	respiratory tract		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure	Skin		
Species	mouse		

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

Source	ECHA
Evaluation	non-sensitizing
Evaluation/classification	Based on available data, the classification criteria are not met.
2	butanone 78-93-3 201-159-0
Route of exposure	Skin
Species	guinea pig
Method	OECD 406
Source	ECHA
Evaluation	non-sensitizing

Germ cell mutagenicity		
No	Substance name	CAS no. EC no.
1	ethanol	64-17-5 200-578-6
Type of examination	in vitro gene mutation study in bacteria	
Species	Salmonella typhimurium	
Method	OECD 471	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
Type of examination	in vitro gene mutation study in mammalian cells	
Species	mouse lymphoma cells	
Method	OECD 476	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
Type of examination	Genotoxicity in vivo	
Species	mouse	
Method	OECD 478	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
2	butanone	78-93-3 201-159-0
Type of examination	in vitro gene mutation study in bacteria	
Species	Salmonella typhimurium	
Method	OECD 471	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
Type of examination	In vitro Mammalian Chromosomal Aberration Test	
Species	rat	
Method	OECD 473	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
Type of examination	In vitro mammalian cell gene mutation test	
Species	Mouse lymphoma cells	
Method	OECD 476	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
Type of examination	In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus	
Species	mouse	
Method	OECD 474	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	

Reproduction toxicity		
No	Substance name	CAS no. EC no.
1	ethanol	64-17-5 200-578-6
Route of exposure	oral	
NOAEL		
Type of examination	2 generation study	
Species	mouse	
Method	OECD 416	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

Route of exposure	inhalational
NOAEL	>= 20000 ppm
Type of examination	Prenatal Developmental Toxicity Study
Species	rat
Method	OECD 414
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

2	butanone	78-93-3	201-159-0
Route of exposure	inhalational		
Type of examination	Prenatal Developmental Toxicity Study		
Species	rat		
Method	OECD 414		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	butanone	78-93-3	201-159-0
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

STOT - single exposure	
No data available	

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Route of exposure	oral		
Duration of exposure	14		week/s
Species	rat		
Target organ	kidneys		
Method	OECD 408		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	butanone	78-93-3	201-159-0
Route of exposure	inhalational		
Species	rat		
Method	OECD 413		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Aspiration hazard	
No data available	

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		14200	mg/l

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

Duration of exposure		96	h
Species	Pimephales promelas		
Method	EPA		
Source	ECHA		
2	butanone	78-93-3	201-159-0
LC50		2993	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		

Toxicity to fish (chronic)			
No data available			

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
EC50		5012	mg/l
Duration of exposure		48	h
Species	Ceriodaphnia dubia		
Method	ASTM Standard E 729-80		
Source	ECHA		
2	butanone	78-93-3	201-159-0
EC50		308	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
NOEC		9,6	mg/l
Duration of exposure		9	day(s)
Species	Daphnia magna		
Source	ECHA		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
EC50		275	mg/l
Duration of exposure		72	h
Species	Chlorella vulgaris		
Method	OECD 201		
Source	ECHA		
2	butanone	78-93-3	201-159-0
EC50		2029	mg/l
Duration of exposure		96	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No data available			

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

Type	aerobic biodegradation		
Value	appr.	84	%
Duration		20	day(s)
Source	ECHA		
Evaluation	readily biodegradable		
2	butanone	78-93-3	201-159-0
Type	aerobic biodegradation		
Value		98	%
Duration		28	day(s)
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
	log Pow	-0,35	
	Reference temperature	24	°C
	with reference to	pH 7,4	
	Method	OECD 107	
	Source	ECHA	
2	butanone	78-93-3	201-159-0
	log Pow	0,3	
	Reference temperature	40	°C
	Method	OECD 117	
	Source	ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Used, completely emptied, packaging may be disposed of or passed to recovery systems in compliance with national and local provisions related to waste legislation. Like the unused product, the packaging that has not been emptied, may be disposed of or passed to recovery systems in compliance with national and local provisions related to waste legislation.

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3
 Classification code F1
 Packing group II
 Hazard identification no. 33
 UN number UN1210
 Proper shipping name PRINTING INK RELATED MATERIAL
 Special Provision 640 640C
 Tunnel restriction code D/E
 Label 3

14.2 Transport IMDG

Class 3
 Packing group II
 UN number UN1210
 Proper shipping name PRINTING INK RELATED MATERIAL
 EmS F-E, S-D
 Label 3

14.3 Transport ICAO-TI / IATA

Class 3
 Packing group II
 UN number UN1210
 Proper shipping name Printing ink related material
 Label 3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)	
According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.	
REACH candidate list of substances of very high concern (SVHC) for authorisation	
According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.	
Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES	
The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances	
This product is subject to Part I of Annex I, risk category:	P5b

Trade name: 77001-00117, solvent

Product no.: 77001-00117

Current version : 1.0.0, issued: 22.07.2021

Replaced version: -, issued: -

Region: IE

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)		
VOC content	100	%
VOC-value	790	g/l

Other regulations
Adhere to the national sanitary and occupational safety regulations when using this product.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH066 Repeated exposure may cause skin dryness or cracking.
H336 May cause drowsiness or dizziness.

Creation of the safety data sheet

UMCO GmbH - D-21107 Hamburg, Georg-Wilhelm-Strasse 187, Tel.: +49(40)555 546 300, Fax: +49(40)555 546 357, e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 776833